











EF2600FW

EF2600FW



-  **4-stroke OHV engine**
Compact size, high power, low fuel consumption & low noise level.
 -  **Brushless generator**
Maintenance free.
 -  **Oil warning system**
Engine stops automatically when oil level (pressure) has fallen below the prescribed level.
 -  **Non-fuse breaker**
Easier 'on' & 'off' of AC output with circuit breaker.
 -  **Auto decompressor**
Light recoil starting.
 -  **DC output capability**
Convenient for battery charging.
 -  **Fuel gauge**
Fuel level confirmation at a glance.
 -  **Voltmeter**
Voltage confirmation at a glance.
 -  **Frame**
Easy to carry & solid protection.
- On all models
 On some models

Specification Sheet

Generator		Features	
Type	Bi-polar revolving field / with damper winding	Brushless	○
Rated voltage (V)	230	Voltage regulator	Condenser
Frequency (Hz)	50	Auto decompressor	○
Rated output (kVA)	2.0	Dual voltage	×
Max output (kVA)	2.3	Circuit breaker system	AC:N.F.B / DC:Protector
DC output	12V / 8.3A	Fuel level gauge	○
Engine		Oil level warning system	○
Type	MZ175 : 4-stroke OHV forced air cooled	Voltage meter	○
Starting system	Recoil	Pilot lamp	×
General		Acces.	
L*W*H (mm)	510*415*425	AC Plug	×
Dry Weight (kg)	41	DC charging cord	○
Fuel tank capacity(full)(l)	12.0		
Operating hours (Hr)	10.6		
Noise Level (db A)(7m)	65.0		
		Receptacle	 15A250V

Please read your owner's manual and all labels before operation.