













# EF5500FW


## EF5500FW



-  **4-stroke OHV engine**  
Compact size, high power, low fuel consumption & low noise level.
-  **Brushless generator**  
Maintenance free.
-  **Oil warning system**  
Engine stops automatically when oil level (pressure) has fallen below the prescribed level.
-  **Non-fuse breaker**  
Easier 'on' & 'off' of AC output with circuit breaker.
-  **Auto decompressor**  
Light recoil starting.
-  **Auto choke**  
Easier starting.
-  **Fuel gauge**  
Fuel level confirmation at a glance.
-  **Voltmeter**  
Voltage confirmation at a glance.
-  **Electric starter**  
Easier starting.
-  **Frame**  
Easy to carry & solid protection.

-  On all models
-  On some models

## Specification Sheet

Generator		Features	
Type	Brushless, Condenser Comensation, Synchronous AC Generator/Single Phase	Cell Motor	×
Rated voltage (V)	230	Dual Voltage	×
Frequency (Hz)	50	V Meter & Hour Meter	○
Rated output (kVA)	3.8	Oil Warning Lamp	○
Max output (kVA)	4.6	Economy Idle	×
<b>Engine</b>		Auto Choke	×
Type	MZ360 : 4-stroke OHV forced air cooled	Fuel Level Gauge	○
Starting system	Recoil	AVR	×
<b>General</b>		Output mode Switch	×
L*W*H (mm)	670*535*565	Fuel Cut	○
Dry Weight (kg)	80	Wheel Kit	Option
Fuel tank capacity(full)(l)	28	Remote Control Kit	
Operating hours (Hr)	1/2 Load: 17.5 Rated Load:12.0	Battery	×
Noise Level (db A)(7m)	70.7	GFCI Receptacle	×
		<b>Receptacle</b>	 15A250V

Please read your owner's manual and all labels before operation.